

## GLASS-CLAD POLYCARBONATE 1-3/8" NO SPALL (LEVEL 5)

PART#: GCP-005-1375-NS\_L5

PRODUCT LINE: GLAZING

### DESCRIPTION

GCP or Glass-Clad-Polycarbonate No Spall is a series of glass units that are laminated together, bonded with either poly-urethane or polyvinyl butyral layers. A layer of polycarbonate is then added to the Witness Side, often called the Secure Side of the make-up to ensure a projectile meeting the rating of the glazing unit is captured with no penetration. The polycarbonate layer also protects against any spall particles of glass projected outwards, which is where the term "No-Spall" is applied.

### OPTIONS

- Reflective Glass
- One-Way Mirror
- Translucent White Interlayer (Frosted Layer)
- Tint (Gray, Bronze, Green, & Blue)
- Insulating Units
- Low E

More to choose from – Please inquire, as the size and thickness may not be available for every option.

### RATINGS


- U.L. Level 5 – 5-7.62 mm Rifle Military Ball

### STANDARDS

- NSI Z971-1984 Safety Glazing Materials for Building
- ASTM C 1036 Standard Specifications for Flat Glass
- ASTM C 1172 Standard Specification for Laminated Architectural Flat Glass

#### THREAT SIDE

#### SECURE SIDE



1. 3/8" Glass
2. 0.025 Urethane
3. 3/8" Glass
4. 0.025 Urethane
5. 1/4" Glass
6. 0.05 Urethane
7. 1/4" Mar Resistant Polycarbonate

For any Tint, or Low E, 1/8", 3/16", 1/4" glass panels must be used. For this Make-up, the Tint, Low-E, or Mirror Pane can be applied to Layer 5 only.

### PROPERTIES & SPECIFICATIONS

Protection	U.L. Level 5 - 7.62 mm RMB
Ballistic Data	Velocity 1: 2750 ft/s Velocity 2: 3025 ft/s
Shots	1
Light Transmission	67%
Nominal Thickness	1 3/8"
Weight	14.78 lbs/sqft
Dimensional Tolerance	ASTM C 1349